



# Heartwood™ Pro Shingles

## Single 7" Perfection Shingles

**General Description:** Heartwood PRO Single 7" Perfection Shingles provide the look of wood shingles, but do not require the upkeep common to wood. Heartwood PRO Shingles are manufactured with a true-to-life cedar shingle texture molded directly from natural wood shingles. Heartwood PRO Shingles are an ideal product for remodeling, new construction for single family homes, multi-housing projects and light commercial developments.

### Styles:

Profile	Finish	Panel Dimensions	Panel Projection	Wall Thickness (Nominal)	Lock Design	Colors	Accessory Pocket
7" Perfection Shingle	Cedar	7" x 6' 1-1/4" Single Course	3/4"	.080" to .090"	Molded continuous perimeter lock for seamless	15	3/4"

**Colors:** Heartwood PRO Shingle siding is available in the industry's widest selection of colors. All colors are Spectrophotometer controlled.

Ash	Harbour	Rustic Clay	Twilight Gray
Canyon Ridge	RiverStone	Smokestone	White

**Accessories:** Wolverine® by CertainTeed manufactures a wide range of siding accessories that are compatible with Heartwoods siding colors. Accessory products include installation components, soffit, window and door trim, and corner systems. Heartwood Shingles use 3/4" pocket accessories.

**Composition:** Heartwood PRO Shingles siding is produced using a modified polypropylene copolymer.

**Technical Data:** Heartwood PRO Shingles siding is in compliance with ASTM specification for Polypropylene (PP) Siding D 7254 and the requirements of the 2015, 2018, and 2021 and 2024 International Residential Code and International Building Code, the 2020 and 2023 Florida Residential Code and Florida Building Code, the 2019 and 2022 California Residential Code and California Building Code. Heartwood PRO Shingles siding meets or exceeds the properties noted in Table 1.

Table 1

ASTM E 84	Meets Class C flame spread requirements as tested according to ASTM E84.
NFPA 268	Radiant Heat Test – Ignition Resistance of Exterior Walls – Conclusion that Wolverine met the conditions for allowable use as specified in section 1406 of the International Building Code.

**Important Fire Safety Information:** When rigid polypropylene is exposed to significant heat or flame, the polypropylene will soften, sag, melt or burn, and may thereby expose material underneath. Care must be exercised when selecting underlayment materials because many underlayment materials are made from organic materials that are combustible. You should ascertain the fire properties of underlayment materials prior to installation. All materials should be installed in accordance with local and state Model Building Codes and fire regulations.

**Wind Load Testing:** Wolverine® Heartwood PRO Single 7” siding has been tested per ASTM D 5206 standard test method for wind load resistance to withstand negative wind load pressures and their mph equivalents as shown in the chart below. All products exceed industry standards for wind load performance. Check with your local building inspector for wind load requirements in your area for the type of structure you are building

Table 2

Product	Fastener Spacing	2015/2018 IBC/IRC		2021/2024 IBC/IRC			
		Standard Design Pressure Rating	Maximum Windspeed (mph)		Standard Design Pressure Rating	Maximum Windspeed (mph)	
			ASD	ULT		ASD	ULT
Single 7” Shingles	Nails 10" o.c.	105.0	209	270	95.7	199	257

\* Windload calculations based on ASTM D3679, ASCE 7-10, 30ft High, Exposure B

**Documents:** Wolverine Heartwood PRO Siding meets the requirements of one or more of the following specifications.

- VSI/Intertek **TBD**
- Conforms to ASTM D7254 Florida BCIS Approval FL **TBD**
- ICC-ES Evaluation Report **TBD**

For specific product evaluation/approval information, call 800-233-8990.

**Installation:** Complete instructions for installing Wolverine Heartwood PRO siding are available in the “Installation Instructions” manual available from Wolverine. Please review this manual prior to installation, it contains important installation requirements

**Warranty:** Wolverine supports Heartwood PRO Shingles siding with a Lifetime Limited Warranty to the original homeowner. The warranty is transferable if the home is sold.

**Sample Short Form Specification:** Siding as shown on drawings or specified herein shall be Heartwood PRO 7" Perfection Shingles as manufactured by Wolverine Siding, Malvern, PA. The siding shall be .090” nominal thickness. Installation shall be in accordance with manufacturer's written instructions.

**Three-part Format Specifications:** Long form specifications in three-part format are available on the Wolverine website at [www.wolverinesiding.com](http://www.wolverinesiding.com).

